

# TPS<sup>®</sup> COURT SURFACES

## TPS<sup>®</sup> 5000 LINE PAINT

### DESCRIPTION

TPS 5000 Line Paint is an acrylic paint specifically designed for use on acrylic coated surfaces, asphalt or concrete pavements.

### USES

TPS 5000 Line Paint is used for line markings on tennis courts, playgrounds and recreational areas. TPS 5000 Line Paint can be used for exterior or interior markings.

### SURFACING PREPARATION

Surfacing should be thoroughly cleaned and free from oil, grease, dirt and other foreign matter. New asphalt should cure for a minimum of 14 days and concrete should cure for a minimum of 28 days, if paint is applied over uncoated surface.

### MIX DESIGN

Use TPS 5000 Line Paint as is – do not dilute. When ordering TPS 5000 Line Paint, figure 1 gallon per tennis court or 500 lineal feet per gallon.

### APPLICATION

TPS 5000 Line Paint can be applied to properly cleaned, dry asphalt pavements or color-coated areas by brush or roller.

### CLEAN-UP

Rinse tools with water soon after using.

### SHELF LIFE

Approximately 12 months.

### PHYSICAL PROPERTIES

Weight/Gallon	11 lbs. per gallon
Drying Time	Touch: 30-60 minutes
Ready to Play:	24 Hours
Application Temperature:	50 degrees F & rising.

### PRECAUTIONS & LIMITATIONS

Keep from freezing. Harmful if swallowed. Read material safety data sheets. This product will not prevent pavement cracks from occurring or re-occurring. Do not apply if surface temperature is less than 50F or more than 140F. Do not apply over tar emulsion sealers. Apply only when ambient temperature is 50F and rising. Do not apply when rain is imminent.

### SHIPPING WEIGHT

1 gallon pail	12 lbs.
---------------	---------

Limited Warranty: This product is guaranteed to be of the kind and quality described in its specifications. All other warranties are specifically excluded and the manufacturer shall not be liable for any consequential damages. Under no circumstances shall the manufacturer's liability exceed the purchase price of any materials deemed to be defective under this warranty. Warranty will be voided on multi-coated applications if material made by other manufacturers that has not been approved by the manufacturer of TPS 5000 products, is used with this product.



### HELLAS CONSTRUCTION, INC.

12710 Research Boulevard Suite 240

Austin, Texas 78759

T: 512.250.2910

F: 512.250.2910

[WWW.HELLASCONSTRUCTION.COM](http://WWW.HELLASCONSTRUCTION.COM)

